

CEMENT PAINT



Product Description

HD Colour Paints Cement Paint is a economic water proof cement paint to give extra protection to buildings in different weather conditions specially designed for exteriors. It is specially formulated for easy mixing and application. This provides a hard, durable coating which resists penetration of moisture and does not rub, flake or peel off from the surface.



Product Features

Economy Colour Coating

Anti fungal and anti algal

Breathable Paint

Anti fungal and anti algal

Good appearance

Surface Prepration

The surface to be painted must be free from all dust, grease, traces of paint flakes, fungus, etc. The surface previously coated with paint must be cleaned thoroughly with a stiff coir brush, to remove dust, dirt chalking or any friable material. This ensures proper adhesion of new paint system. All structural cracks must be open in V shape filled with white cement/cement based plasters. All leakages should be stopped before actual painting. Freshly plastered surface must be allowed to cure completely.

CEMENT PAINT

Curing

one time curing before first coat, 2 - 3 times curing after first coat within next 8-16 hrs. Apply 2nd coat after 8-16 hrs and then again 2 - 3 times curing.

Sheen

Matt Finish

Thinning Properties

1 Kg Cement Paint and water quills like flour and than thin it as per application. We recommend 1kg Cement paint thinned with 1000 ml of water.

Stability of Thinned Paint

To be used with in an hour(Under Standard Conditions)

Opacity

Provides good opacity to the surface, protecting it against all damages.

Coverage

30 - 45 sq ft/kg/coats, on normal masonry surface by brush application.*

Shade

30+ shade available and we can manufacture as customized shade also

Drying Properties

Surface Dry 8-12 Hrs.

Opacity

Provides good opacity to the surface, protecting it against all damages.

CEMENT PAINT

Precautions

- Do not apply when ambient temperature is less than 10°C or if the temperature might drop to this level within 2-4 hrs of application
- Do not paint when it is raining
- Do not over-thin or over-extend the brush
- Do not use saline water for sprinkling
- Avoid application of paint under strong direct sun as it may cause fast drying, brush marks and even patchy surfaces
- If the surface is too absorbent then the first coat may have to be applied with more than usual thinning

***Actual coverage may vary depending on the surface porosity, surface roughness, temperature and application technique.**